

T3 T1 E3 E1 Software
Selectable



Supports Channelization of
Captured E1 Signals into
42 or 32 Independent E1
Channels



Supports Channelization of
Captured T1 Signals into 56
Independent T1 Channels



Supports ISDN, SS7, CAS and
Other Channelized Protocols



Direct Access to All or User-
defined 2 x 28 T1s, 2 x 21,
2 x 16 E1s per Port for
Analysis



Supports BERT, and Capture
and Playback applications



Supports Analysis of Various
Signal Types Including Voice,
Digits, Tones, Fax, Modem, and
Raw Data



T3 T1 E3 E1 Multi-Interface Tester (mTOP™) Analysis and Emulation Hardware

Overview

GL's rack based **Channelized T3E3 Analyzer**, supports 6 T3s (6 * 672 DS0s). Multiple rack units can be stacked together for greater scalability. A T3 (DS3) consists of a total of 28 T1s, or 672 full duplex voice channel. Similarly, an E3 consists of a total of 16 E1s, or 480 full duplex voice channels.

Almost all of GL's T1 E1 Testers can be accommodated into rack based units. A customized 2U rack tProbe™-T1 E1 / Datacom-Analog units, to serve the purpose of handling multiple communications lines and test complex functionalities. For more details, visit <https://www.gl.com/test-high-speed-wan-services-t3-e3-ds3-line.html>.

Main Features

- Analysis/Emulation of T3 (44.736 Mbps) and E3 (34.368 Mbps)
- Analysis/Emulation of ATM, PPP, HDLC, and Frame Relay signalling
- Record / Playback of entire T3 or E3
- Monitoring & generating alarms, and error insertion
- Analysis of all 28 T1s (1.544 Mbps each) per T3 port, or 16 E1s (2.048 Mbps each) per E3 port in Channelized mode
- Analysis of Fractional T1s and E1s, N x T1s or N x E1s
- Analysis of any combination of DS0s (64 kbps each) within the T1s or E1s (for example, each T3 port has 28 x 24 = 670 DS0s for T1 or 21 x 32 = 672 DS0s for E1) with additional applications, such as record-only, one can even record traffic at DS0 levels
- Support for all T1 E1 "basic applications" and "special applications"
- Monitor the T1/E1 line conditions such as frame errors, violations, alarms, frequency, power level, and clock (or frame/bit) slips
- Comprehensive Analysis / Emulation of Voice, Data, Fax, Protocol, Analog, and Digital signals, including Echo and Voice Quality testing



 **GL Communications Inc.**

818 West Diamond Avenue - Third Floor, Gaithersburg, MD 20878, U.S.A
(Web) <http://www.gl.com/> - (V) +1-301-670-4784 (F) +1-301-670-9187 - (E-Mail) gl-info@gl.com

mTOP™ Specifications

Space Requirements

- Height: stacked 2U Rack unit [Total space—2U]
- Length: 16 Inches
- Width: 19 Inches

Embedded PC Specifications

- 2U 19" Rack Mount Enclosure w/Rails, Multiple Interface TDM/Optical/Packet w/Single Board Computer (SBC)
- Intel Core i3, Win10 Pro OS 64 bit
- USB 3.0 Hub, ATX Power Supply
- Min 240GB SSD, 8GB RAM

Connectors for T3/E3

- DS3/E3 750 BNC (Tx, Rx) Ports
- DS1/E1 RJ-48-c (Tx, Rx) for Drop/Insert
- MCX External Clock Ports
- USB 2.0 Connected to a USB HUB
- Internally powered by Power Supply
- 1000 Mbps Ethernet Port

T3/E3 Specifications

T3 (DS3) / E3 Line Interface

Output Amplitude	800mV ± 50mV
Input Impedance	75 Ohms unbalanced (BNC)
Line Code	B3ZS (T3), HDB3 (E3)
Terminate Input Level	0.09Vp – 0.85Vp
Monitor Input Level	0.025Vp – 0.08Vp

T3 E3 Signal

- Up to 56 T1s per T3 unit (or 1*2* 28)
- Up to 42 E1s per T3 unit (or 1*2* 21)
- Up to 32 E1s per E3 unit (or 1*2* 16)

T3/E3 Specifications (Contd.)

Clock Source

Internal	± 1 PPM @25C [± 4.5 ppm (includes ageing, stability)]
Recovered	Clock recovered from receiver
External	TTL Level signal High Speed (T3 (DS3) / E3 Rate) Low Speed (2KHz, 8KHz, 2MHz, 1.5MHz) Recovered from Inserted T1 or E1

T3 (DS3) / E3 Transmitter

T3 (DS3) / E3 Payloads	Framed T3 (DS3) / E3 Data, Unframed T3 (DS3) / E3, Idle, AIS
T3 Framing Modes	Unframed M13 (ANSI T1-107 – 1995) Structured (Channelized), and Unstructured (Unchannelized) C-bit (ANSI T1-107 – 1990) - Structured (Channelized), and Unstructured (Unchannelized)

Unchannelized T3 supports subrate and scrambling formats for Digital Link, ADC/ Kentrox, Larscom, Adtran, and Verilink data service units (DSUs)

E3 Framing Modes	Unframed, E13 (for E3) - Structured (Channelized), and Unstructured (Unchannelized)
Framed T3 (DS3) / E3 Unstructured Payload	Raw Data from File, ATM Cells (only for T3), HDLC Frames, BERT Patterns
Unframed E3 Payload	Raw Data from File, BERT Patterns
Channel Structure	T1, E1 (DS1) (ITU-T G.747)
BERT Patterns	QRSS, 2 ⁶ -1, 2 ⁹ -1, 2 ¹¹ -1, 2 ¹⁵ -1, 2 ²⁰ -1, 2 ²³ -1, User Defined upto 32-bits, other static patterns
T1 (DS1) Payload	Inserted T1, AIS, Loopback, BERT Patterns (future)
E1 Payload	Inserted E1, AIS, Loopback, BERT Patterns (future)
Loopbacks	Complete T3 (DS3) / E3 Signal, Selected T1s/E1s from incoming T3 (DS3) / E3



T3/E3 Specifications

T3(DS3)/E3 Receiver		Supported Protocols	
T3 (DS3) Framing Format	M13 (ANSI T1-107 – 1995), C-bit (ANSI T1-107 – 1990), Unframed, Structured (Channelized), and Unstructured (Unchannelized)	T3 (DS3) / E3 Payloads	Framed T3 (DS3) / E3 Data, Unframed T3 (DS3) / E3, Idle, AIS
E3 Framing Format	E13, Unframed, Structured (Channelized), and Unstructured (Unchannelized)	Channelized Protocols	High-Level Data Link Control (HDLC) Point-to-Point Protocol (PPP), RFC 1662, Multilink PPP (MLPPP), RFC 1990 Frame Relay, RFC 1490 Multilink support over Frame Relay (FRF.12) and MLPPP ATM IMA GSM, TRAU, GPRS, UMTS over ATM SS7, ISDN, CAS, SS1, SSM V5.x, DCME, FDL (T1 Interface only)
Channel Structure	T1 (DS1) /E1 (ITU-T G.747)	UnChannelized Protocols (Unstructured)	PPP, ATM, Frame Relay
Framed T3 (DS3) / E3 Unstructured Payload	Raw Data Captured to File, ATM Analysis (only for T3), HDLC Frames Analysis, BERT Patterns Measurement		
Framed T3 (DS3) / E3 Structured Payload	Raw Data Captured to File, BERT Patterns Measurement, Drop Selected T1(s) / E1(s)		
T1 E1 Transmit / Receiver		Miscellaneous	
	Bit error rate testing (BERT) pattern generation and detection per channel	T3 (DS3) / E3 Line Rate Offset	± 50 PPM in 1 ppm Steps
	Transmit Tone, Transmit Gaussian Noise, Transmit Multiframe	Level Measurement	Supported
	Transmit Signalling Bits, and Rx-to-Tx loopback	Frequency Measurement	± 1 PPM
Compliance	G.703 Physical/Electrical Characteristics GR-499-CORE Physical/Electrical Characteristics G.821 Bert Analysis G.742 Multiplexing G.751 Multiplexing	T3 (DS3) Error Add	Payload Bit, Frame Errors, P-bit, C-bit, EXZ (for T3);
		E3 Error Add	Frame Errors, Code Violation (CV) Error, EXZ, Payload Bit
		T3 (DS3) Alarm Generation	LOS, AIS, RAI (X-bit), Idle, FEAC Codes (Loopback and alarm/status codes)
		T3 (DS3) Alarm Monitoring	LOS, LOF, AIS, Idle, RAI (X-bit), EXZ
		E3 Alarm Generation	LOS, OOF, RAI (X-bit);



T3/E3 Specifications

Miscellaneous (*Continued*)

E3 Alarm Monitoring	LOS, LOF, AIS, RAI (X-bit), EXZ
T3 (DS3) FEAC Codes	Alarm status codes, loopback codes with channel indicator for T1
LED Indicators	LOS, LOF, ERR, PGM

Mechanical

Power Supply	100-240V, 5A, 50/60Hz
Operating temperature	0° C to 40 ° C
Storage temperature	10° C to 70 ° C
Relative humidity	10 % min, 90 % max, non-condensing

Functional Specifications

- DS3/E3 multiplexing from T1/E1
- DS3/E3 Playback and Capture
- DS3/E3 Protocol Analysis
- DS3/E3 Bert Analysis
- Sending DS3/DS1 SNMP Traps to Network Operation Center (NOC)

tProbe™ Specifications

Basic Software

VF Options

- Speaker
- Drop and Insert
- VF In / Out TS settings

Monitoring Options

- Monitor T1/E1 Line
- Byte Values & Binary Byte Values
- Signaling bits, Power Level, DC Offset, & Frequency
- Multi-frames, and Real-time Multi-frames
- T1/E1 Data as Real-time Bitmap
- Time-slot Window
- ASCII Timeslot Display
- Oscilloscope & Power Spectral
- Active Voice Level

Intrusive Testing

- Bit Error Rate Test
- Enhanced Bit Error Rate
- ATM BERT
- Transmit Tone
- Transmit Gaussian Noise
- Transmit Multiframe
- Transmit Signaling Bits
- Precision Delay Measurement
- Rx-to-Tx Loop back
- Error Insertion

Windows Client / Server

- w/ Remote access to T1/E1 server using Clients - C++, TCL, C#
- Dual VF Tx/Rx



GL Communications Inc.

818 West Diamond Avenue - Third Floor, Gaithersburg, MD 20878, U.S.A

(Web) <http://www.gl.com/> - (V) +1-301-670-4784 (F) +1-301-670-9187 - (E-Mail) gl-info@gl.com

tProbe™ Specifications

Optional Software

Protocol Analysis

- ISDN, HDLC, SS7, CAS, GSM, GPRS, UMTS, GR303,
- Frame Relay, ATM, PPP, TRAU, CDMA, DCME, T1,
- E1 Maintenance Data Link (SaHDLC and SSM), SS1
- Facility Data Link , V5.x , Fax, Modem

Protocol Emulation

- ISDN, SS7, ISUP Conformance Scripts, GSM Abis,
- GSM A, MAP, CAP, INAP, MLPPP, CAS
- TRAU, SS1, Multi-link Frame Relay Emulation
- Inverse Multiplexing over ATM

WCS Modules

- Tx/Rx files, digits, Protocol Emulation
- Multi-channel BERT,
- DSP operations, Dynamic DSP capability
- FAX Emulation over T1/E1 and Analog Lines

Record / Playback Files—Manual, Automated

Capture, Analysis, & Emulation - DTMF / MF / MFRC2, Digits, Tones, Voice, Fax, Modem, Raw Data

Voice Band Analysis Software

Call Data Records

Multi-Channel BERT

Jitter Generation, Jitter Measurement, & Pulse Mask

Protocol Identifier, Traffic Classifier

Echo Cancellation Testing / Compliance -Manual, Semi-automated, & Automated –G.168, G.160, G.169

- Measure Loop Delay/ERL
- Delay Attenuate Timeslots
- Digital Echo Canceller Simulator
- Audio Processing Utility (APU)

Signaling Transitions Recording

Real-time Strip Chart

Real-time Multichannel Audio Bridge

Multiplex / Demultiplex Software

Network Surveillance, Voice Quality Testing

Physical Interface

Ethernet Connector	(1) RJ-45 10/100 Ethernet Jack
T1/E1 Connectors	(2) RJ-48c Jacks
Audio Connectors	(4) 3.5 mm Balanced (Stereo) or Unbalanced (Mono) Audio Jacks (TX & RX)
External Clock Connector	(1) MCX Coaxial Jack
External Power Connector	(1) Coaxial DC Power Jack (mates with 5.5mm x 2.1mm coaxial plug)

External Power Requirements

Power Adapter Requirements	+5V @ 2A Max Power to the Center Ring
----------------------------	---------------------------------------

T1/E1 Line Interface

Framing Formats	Unframed, D4 (T1) , ESF(T1), ESF(J1), CAS (E1), FAS(E1), CRC4 Hardware Compliant: SLC96, T1ESF ZBTSI
Line Code format	AMI, B8ZS (T1) or HDB3 (E1)
Internal Clock Specification	Standard: +/- 3ppm Optional: +/- 1ppm
Output Clock Source	Internal (+/- 1 ppm or 3 ppm), Recovered, External Clock
T1 Output Level	T1: 3.0V Base to Peak Selectable 0-655Ft Pulse Equalization Setting; Tx Capability - DSX-1 Outputs (to 655 feet)
E1 Output Level	E1: 3.0V ± 0.3V Base to Peak
Input Level	75 mV to 6V base to peak or -30 dBx to -6 dBx
Line Built Out Selections	0dB, -7.5dB, -15dB, -22.5dB – for T1 only
Loopback	Normal (Outward and Inward) Cross-Port Transmit Loopback Cross-Port Through Loopback



818 West Diamond Avenue - Third Floor, Gaithersburg, MD 20878, U.S.A
(Web) <http://www.gl.com/> - (V) +1-301-670-4784 (F) +1-301-670-9187 - (E-Mail) gl-info@gl.com

tProbe™ – Specification

Transmit

T1/E1 Interface Hardware Compliance	ANSI: T1.403.1995, T1.231-1993, T1.408 AT&T: TR54016, TR62411 ITU: G.703, G.704, G.706, G.736, G.775, G.823, G.932, I.431, O.151, Q.161 ITU-T: Recommendation I.432-03/93 B-ISDN User-Network Interface-Physical Layer Spec ETSI: ETS 300 011, ETS 300 166, ETS 300 233, CTR12, CRT4 Japanese: JTG.703, JTI.431, JJ-20.11 (CMI Coding Only)
BERT Pattern Generation	Pseudorandom patterns: (63) 2^6-1 , (511) 2^9-1 , (2047) $2^{11}-1$, (32767) $2^{15}-1$, (1048575) $2^{20}-1$, (8388607) $2^{23}-1$, QRSS. Hardware Compliant: T1 In-Band Loop Code Generation and Detection Fixed patterns: All Ones, All Zeros, 1:1, 1:7, 3 in 24, User Defined 24- Bits Hardware Compliant: User pattern of up to 32 bits in length
Alarm Insertion	Blue, Yellow, Remote, Distant Multiframe Hardware Compliant: Bit 7 Zero Suppression D4 Yellow: 1 in S bit of frame 12 AIS-CI Code, ESF-RAI CI Code Receive Carrier Loss: 0's for 2047 or 255 bits (For E1 only)
Error Insertion	BPV, Bit Error, Frame Error, CRC Errors, Burst Frames, Fixed Error Rate, Random Error Rate, auto logic from 10^{-2} to 10^{-9} for selectable 56K or 64Kps channels.
Drop and Insert	Any contiguous set of digital timeslots and/or audio input
Facility Data Link	T1 ESF Mode: Transmit/Receive Messages, Bit- Oriented Messages, and Files.
Zero Suppression	B7 Stuffing, Transparent, & B8ZS (T1)
Signaling Frequency Offset	Robbed-Bit or Clear Channel T1: +/- 615Hz E1: +/- 615Hz

Receive

Input Impedance	100 ohms for Terminate and Monitor (T1) 120 ohms for Terminate and Monitor (E1) > 1K ohms for Bridge
Terminations	Terminate, Monitor, Bridge
T1 Input Frequency	1.544MHz +/- 20 KHz
E1 Input Frequency	2.048Mhz +/- 20 KHz
Frequency Measurement	+/- 1ppm
Error Detection	Frame Error, CRC Error, BPV Error, Logic Error, Frame Alignment Error Hardware Compliant: * 10 or 24 bits for sync time * 2/4, 2/5, or 2/6 frame bit in error frame select * Frame error bit corruption for 1 or 3 frame bits * E-Bit Error * Line Code Violation
Alarm Detection	T1 - D4 Yellow Alarm, ESF Yellow Alarm Yellow Alarm (B2 Suppressed-2nd MSB) Yellow Alarm (S-Bit) Yellow Alarm (00FF in FDL) Blue Alarm (Framed or Unframed All Ones) E1 - Remote Alarm Distant Multi-Frame Alarm Signaling All Ones Unframed All Ones Hardware Compliant: J1 Yellow Alarm
Intrinsic Jitter	Meets Jitter Tolerance: Meets AT&T TR 62411 (Dec. 90) ITU-T G.823 Jitter Transfer: Meets AT&T TR 62411 (Dec. 90)
Input Range	T1: Terminate, 0 to 36dB (Long Haul), DSX Monitor, Bridge Hardware Compliant: Terminate, 0 to 15dB (Limited Long Haul), DSX Monitor 20 dB, 26 dB, 32 dB E1: Terminate, 0 to 43dB (Long Haul), DSX Monitor, Bridge Hardware Compliant: Terminate, 0 to 13 dB (Short Haul), DSX Monitor 20 dB, 26 dB, 32 dB



818 West Diamond Avenue - Third Floor, Gaithersburg, MD 20878, U.S.A

(Web) <http://www.gl.com/> - (V) +1-301-670-4784 (F) +1-301-670-9187 - (E-Mail) gl-info@gl.com

tProbe™ – Specification (Contd...)

Display and Logging

BERT	Bit Errors, Bit Error Rate, Error Seconds, Error Free Seconds, %EFS, Severely Error Seconds, %SES, Degraded Minutes, %Dmin, Loss Pattern Sync Count, Loss of Sync Seconds, Available Seconds, %Available Seconds, Unavailable Seconds, Bipolar Violations, BPV Rate, BPV Seconds, BPV Free Seconds, Frame Errors, FE Rate, FE Seconds, FE Free Seconds, with Detailed logging into disk file.
Alarms	Resync In Progress, Loss of Signal, Blue Alarm, Change of Frame Alignment, Bipolar Violation, Frame Error, Carrier Loss, Yellow Alarm, Out of Frame Events Counter, Error Super frame Counter, Bipolar Violations, Remote Alarm, Distant Multiframe Alarm, Signaling All Ones, CAS Multiframe Error, CRC4 Error.

Buyer's Guide

Order information of T3 T1 E3 E1 Multi Tester

[MT003](#) - mTOP™ 2U Rack Mount Enclosure w/SBC

[TE3001](#) – Dual T3 E3 / T1 E1 Hardware USB Base Unit

[PTE001](#) – tProbe™ T1 E1 Base Unit

For more details on product list, refer to [T1E1 product list](#)

Order information of 6 x T3 E3 System

[TE3005](#) – Rack Enclosure for T3/E3 System – up to 6 T3/E3s.

2U - 19" Rack Enclosure, Power Supply, Fans, 4 Port USB Hub, Cables and Accessories, Accommodates three (3) Dual T3/E3 USB Units.

SA005z – 19" 1U Rack Mount PC w/o Monitor, but with Keyboard, Mouse, Xeon 8 GB, 500 GB

For more details on product list, refer to [T3E3 product list](#)



GL Communications Inc.

818 West Diamond Avenue - Third Floor, Gaithersburg, MD 20878, U.S.A

(Web) <http://www.gl.com/> - (V) +1-301-670-4784 (F) +1-301-670-9187 - (E-Mail) gl-info@gl.com