

GL Communications Inc.

T1/E1 Accessories Price List

Revised: May 3, 2018

| Part Number | Description | Notes |
|---------------------------|---|---|
| SA000 SA000a SA000c | High Stability Internal Clock for Single Ultra Cards High Stability Internal Clock for Dual Ultra Cards High Stability Internal Clock for Dual Laptop Analyzers | Upgrades Internal clock to ± 1 ppm stability Upgrades Internal clock to ± 1 ppm stability Upgrades Internal clock to ± 1 ppm stability (Standard stability rating is ± 2.5 ppm) |
| SA001 | Bantam Cable | 12 ft Bantam plug to Bantam plug Cable |
| SA002b | Dual 75/120 Ohm Transformer | DUAL: 75 ohm BNC to 120 ohm RJ48C |
| SA004e | T1/E1 Accessory Kit 1 | Includes Common to all platforms SA007d Dual Bantam to RJ-45 Cables (2) SA010d Bantam-to-EZ Hook Prongs (1) SA010b 5' Bantam-to-BNC (2) SA010e Terminating Plugs - 100 Ohms T1 & 120 Ohms E1 (2 ea) SA007e RJ-45 Y Bridge (2) SA007k 3.5 mm Dual Mono Plug 3.5 mm Stereo Jack "Y" Cable (1) SA007f RJ-45 to RJ-45 Female to Female (2) SA017A RJ-45 to RJ-45 Straight Cable (2) SA017B RJ-45 to RJ-45 Crossover Cable (2) |
| SA004f | T1/E1 Accessory Kit 2 | For tProbe and T1 E1 Express platforms Includes SA004e and SA007j 3.5 mm Stereo Plug to 3.5 mm Stereo Plug Cable (2) |
| SA004g | T1/E1 Accessory Kit 3 | For Universal and USB T1 E1 platforms Includes SA004e and SA011c 3.5 mm Mono Plug to 3.5 mm Mono Plug (2) |
| SA005d | Notebook PC | Notebook PC – minimum specs i7 or i5, 8 or 16 GB RAM, 500 GB HD or 256 SSD, Win 10/64 Pro, 3 or 4 USB ports |
| SA005e | Mini-Tower (Desktop) PC – i7 | PC w/o Monitor or Keyboard |
| SA005z | Rack PC, 1U, Xeon | 19" Rack mount PC w/o Monitor, but with Keyboard and Mouse, Xeon 8 GB, 500 GB SSD, with mounting rail and bezel, Dimensions H 1.75" x W 17.24" x L 21.8", Intel |
| SA005m | Rack PC, 1U, Xeon | 19" Rack mount PC w/o Monitor, but with Keyboard and Mouse, Xeon 8 GB, 500 GB SSD, with mounting rail and bezel, Dimensions H 1.75" x W 17.24" x L 17", ABMX |
| SA005n | Rack PC, 1U, Xeon | 19" Rack mount PC w/o Monitor, but with Keyboard and Mouse, Xeon 8 GB, 500 GB SSD, with mounting rail and bezel, Dimensions H 1.75" x W 17.24" x L 14", ABMX |
| SA005p | Portable Lunchbox PC | Portable, Xeon 8GB, 500 GB SSD, 2 x PCIe x8, Dimensions H 14.5" x W 16.46" x L 6.96" |
| SA005r | Rack PC, 2U, Xeon - Standard | 19" Rack mount PC w/o Monitor, but with Keyboard/Mouse, Xeon 8 GB, 500 GB SSD, 1 Processor (Socket), 8 PCIe slots, Redundant PS, with mounting rail and bezel, Dimensions H 3.44" x W 16.93" x L 27.95" |
| SA005s | Rack PC, 2U, Xeon - Super | Same as SA005r, but 1 TB, 16 GB, Dual Processor, with RAID Option |

818 West Diamond Avenue - Third Floor. Gaithersburg, MD 20878 ● (V) 301-670-4784 (F) 301-670-9187

Web Page Address: <http://www.gl.com/> ● E-Mail Address: gl-info@gl.com

Prices are subject to change

GL Communications Inc.

T1/E1 Accessories Price List

Revised: May 3, 2018

| | | |
|----------|---|---|
| SA005kvm | KVM | 1U, 19" Rack Mount KVM console |
| SA007a | Single Bantam to RJ48C - Tx Cable, 10 ft. length | Single bantam plug to RJ48C plug - pins 4,5 |
| SA007b | Single Bantam to RJ48C - Rx Cable, 10 ft. length | Single bantam plug to RJ48C plug - pins 1,2 |
| SA007c | Dual Bantam to RJ48C cable kit - 3 pc. Set | 1 SA007a Tx cable, 1 SA007b Rx cable, 1 SA007e RJ-48 Bridge |
| SA007d | Dual Bantam to RJ48C - Integrated Cable, 10 ft. length | All-in-One cable: Single RJ48C plug to Dual Bantam plugs – 1 Tx and 1 Rx |
| SA007e | RJ48 Y Bridge - Splits one RJ48 into two complete | RJ48 plug to 2 RJ48 jacks – All pins thru |
| SA007f | RJ48 to RJ48 Female to Female Coupler | RJ48 jack to RJ48 jack – All pins thru |
| SA017A | RJ48C to RJ48C Straight Cable, 10 ft. length | RJ48C: pins 1,2 to 1,2; 4,5 to 4,5; 7,8 to 7,8 |
| SA017B | RJ48C to RJ48C Crossover Cable, 10 ft. length | RJ48C: pins 1,2 to 4,5; 4,5 to 1,2; 7,8 to 8,7 |
| SA007i | Bantam to Miniature Phone Plug, 6 ft. length | Single Bantam plug to Single 3.5mm plug |
| SA007j | Mini Phone Plug to Mini Phone Plug Cable, 6 ft. length | Single 3.5mm plug to Single 3.5mm plug |
| SA007k | Mono to Stereo Mini Phone Cable (Y Cable), 6 in. length | Single 3.5mm STEREO jack to 2 Single 3.5mm MONO jacks (L&R) |
| SA007n | Male BNC to Miniature Two Conductor Phone Plug | BNC Male to 3.5mm Mono plug |
| SA007p | BNC to BNC 75 ohm Coaxial Cable, 6 ft. length | BNC to BNC for T3 Signal Interconnect |
| SA007q | SMA to BNC Coaxial Cable, 6 ft. length | SMA to BNC Coaxial Cable, 6 ft. length (for Harris PXE triggering) |
| SA007s | RJ48 Splitter | Permits Drop/Insert and Bridging from RJ48 |
| SA007t | RJ48 High Impedance T-Tap | Permits High Impedance Monitoring of T1 and E1 lines |
| SA007x | Monitoring Kit #1 w/High Impedance T-Tap | 1-SA007t, 1-SA007e, 1-SA017a, 1-SA017b, 1-SA007k |
| SA007y | Monitoring Kit #2 w/RJ-48c splitters for Bridging | 2-SA007e, 2-SA017a, 1-SA017b, 1-SA007k |
| SA007z | Monitoring Kit #3 w/ High Impedance T-Tap and D/I | 1-SA007s, 2-SA017b, 1-SA017a, 1-SA007k |
| SA008a | Bantam to Handset Adapter w/Handset | 4-wire Audio Handset Interface Unit: use with included handset to connect to Audio (VF) interface on GL cards; to talk and listen on a timeslot (NOT necessary on Laptop Analyzer units) |
| SA008b | Telephone Handset Only w/RJ11 Cable | Handset Only for use with Laptop Analyzers |
| SA009 | 2/4 Wire Hybrid | 2-wire to 4-wire Telephone Interface Unit: use with any standard telephone to connect to Audio (VF) interface on GL cards; to talk and listen on a timeslot. NOT for connection to a live PSTN POTS line. |
| PKA001 | 600 Ohm-to-Sound Card Transformer / Adapter | Adapts a Sound Card Interface to 600 Ohm |
| SA040 | Seven Port USB 2.0 Hub | Required for connecting multiple nodes to a single PC |
| SA010a | Bantam to RJ11, 6 ft. length | Single Bantam to Single RJ11 modular |
| SA010b | Bantam to BNC, 8 ft. length | Single Bantam to Single BNC Male plug |
| SA010c | Bantam to Alligator, 8 ft. length | Single Bantam to 3 Alligator Clips |
| SA010d | Bantam to EZ Hooks, 8 ft. length | Single Bantam to 2 EZ-Hook Clips |
| SA010e | Terminating Plugs for 100 and 120 Ohms | Single Bantam Termination Resistor plugs (2 100 ohm Black, 2 120 ohm Red) |
| SA010f | Female Bantam Jack to two 66-Block Bridge Clips | Single Female Bantam to 66 Block Bridge Clips |
| SA011a | One Pair (2) of: Single Bantam plug to single RCA plug cables | Connects SA009 2/4 Wire Hybrid to older GL products with Bantam Audio interface |

818 West Diamond Avenue - Third Floor. Gaithersburg, MD 20878 ● (V) 301-670-4784 (F) 301-670-9187

Web Page Address: <http://www.gl.com/> ● E-Mail Address: gl-info@gl.com

Prices are subject to change

GL Communications Inc.

T1/E1 Accessories Price List

Revised: May 3, 2018

| | | |
|-----------------|---|--|
| SA011b | One Pair (2) of: Single 3.5mm plug to single RCA plug cables | Connects SA009 2/4 Wire Hybrid to current GL products with 3.5mm Audio interface |
| SA011c | 3.5 mm Mono Plug to 3.5 mm Mono Plug (2) | Mono cable for Universal and USB T1 E1 |
| SA012 SA012c | Lunchbox PC Shipping Case w/ Built-in Cart Shipping Case for Notebook PC (SA005d) | Special PC Hard Shell Shipping Case Shipping Case for FAA and ATT |
| SA013 | T1 E1 Training | Software and hardware training |
| SA016c | BNC to MCX Cable for External Clock Connection | Connects to EXT CLK port on all GL PCI cards (Single & Dual) and Dual Laptop Analyzers |
| SA018 | Short RJ-48C Crossover Cable | For Cross-Connect of GL Cards, other eqpt. |
| SA026 | Adobe Audition Multitrack Sound File Viewing & Editing Software (Formerly Cool Edit) | For detailed Viewing and Recording of Multiple Sound Files |
| SA048 SA021 | Goldwave Software File Edit Software | For viewing and recording of sound files To View and Edit Binary Captured Files |
| SA022 | Extended 1 Yr. Software Upgrades and Hardware Warranty, and Comprehensive Support for Basic and Optional Software | Warranty and Comprehensive Support for Hardware and Software = 10% of PO – All T1 E1 Products; includes PC |
| SA029 | Installation CD | Copy of Installation CD – if available |
| SA039 | Recalibration of T1 or E1 Cards or Portable Units | Recalibration of the clock / oscillator on Cards or Portable units |
| SA065 | Printer | Printer |
| SA051 | 19" Inch 1U Rackmount Kit for PXE104 | For Harris PXE104-H-1 |
| SA052 | Sensoray 48-Channel Digital I/O | Sensoray 48-Channel Digital I/O Interface with termination board and power supply |
| SA052-H-1 | Sensoray Pod | Sensoray Pod (Harris part # for SA052) |

| Part Number | Description | Notes |
|------------------------------|--|---|
| Shipping and Handling | | |
| SH001 | Shipping & Handling | Domestic; Per Card |
| SH002 | Shipping & Handling | Domestic; Per System w/ Lunchbox PC |
| SH002a | Shipping & Handling | Domestic; Per System w/ Laptop PC |
| SH002b | Shipping & Handling | Domestic; For Rack PC |
| SH003 | Shipping & Handling | International; Per Card |
| SH004 | Shipping & Handling | International; Per System w/ Lunchbox PC |
| SH004a | Shipping & Handling | International; Per System w/ Laptop PC |
| SH004b | Wire Transfer Charge | International; Per System w/ Rack PC |
| SH005 | Extra Charge for Overnight Delivery - Domestic | Wire transfer charge Priority Overnight Surcharge |
| SH006 | Handling | Handling Charge Only |
| SH007 | Certificate of Origin Charge for Shipments to Israel | Specific to Israel |
| SH008 | For Israel | |
| LOC001 | Letter of Credit Fee | Letter of Credit Fee |

****PC Warranty – excludes damage due to abuse, screen burn-in, improper surge protection, and computer virus**

818 West Diamond Avenue - Third Floor. Gaithersburg, MD 20878 ● (V) 301-670-4784 (F) 301-670-9187

Web Page Address: <http://www.gl.com/> ● E-Mail Address: gl-info@gl.com

Prices are subject to change