

GL Communications Inc.

Digital Central Office Switch Simulator (DCOSS) Price List

Revised: April 13, 2015

Part Number	Description	Notes
	<i>PC Platforms</i>	
DP001	Portable Pentium Lunchbox PC	>1 Ghz; > 1 GB RAM
DP002	Configuration Setup (**waived with PC Purchase**)	
DP004	Pentium Tower PC (without monitor)	>1 Ghz; > 1 GB RAM
DP005B	19" Pentium Rackmount PC	>1 Ghz; > 1 GB RAM
	<i>Trunks</i>	
DET002	Dual E1/T1 (Software Selectable)	requires a full length PCI slot
DET004	Quad E1/T1 (Software Selectable)	requires a full length PCI slot
	<i>Access Interfaces</i>	
DS216	Station Connect; 16-Port	requires a full length PCI slot
DS004	Station Connect Power Supply	for up to 32 phones
DS011	24-Port Telco Breakout Box	Used with APS and FXS
DS100	Analog Telephone	
	<i>Software Options</i>	
DR001	DCOSS Software (**Required**)	R1 Protocol Included
DOR001	Remote Access (Client/Server)	over LAN, WAN, Internet

818 West Diamond Avenue - Third Floor. Gaithersburg, MD 20878 ● (V) 301-670-4784 (F) 301-670-9187
Web Page Address: <http://www.gl.com/> ● E-Mail Address: gl-info@gl.com

Prices are subject to change

GL Communications Inc.

Digital Central Office Switch Simulator (DCOSS) Price List

Revised: April 13, 2015

DO010	Optional Scripted Control for Bulk Call Generate/Receive Generation	includes Scripting GUI Editor
	Signaling Options	
DR010	T1 CAS Protocol	Loop Start & Ground Start
DR007	Digital E&M + European Digital CAS	Brazil, Indonesia, Italy, Holland
DR002	MFC-R2 <i>Countries Available: Argentina, Bahrain, Brazil, China, Colombia, Czech Republic, India, Indonesia, Malaysia, Mexico, Singapore, Thailand, CCITT</i>	includes choice of 2 countries
DR003	Additional MFC-R2 Countries (each)	
DR005	PRI ISDN	Incl. USA, Europe, and Asia
DR042	Signaling System 7 (4 MTP Links) w ISUP, Dual T1/E1 Interface	requires a full length PCI slot
DR052	Signaling System 7 (16 MTP Links) w ISUP, Dual T1/E1 Interface	requires a full length PCI slot
DR035T	SS7 Layer, TUP	Telephone User Part
DR035S	SS7 Layer, SCCP/TCAP	
	Traffic Options	
DOM096	V.90 Modem with 96 ports <i>*Offline Modem Analysis Software – see last page</i>	requires a full length PCI slot
DM001	Fax License (per port)	License per port
DM00F	Quad trunk full fax license	Older generation boards only

818 West Diamond Avenue - Third Floor. Gaithersburg, MD 20878 ● (V) 301-670-4784 (F) 301-670-9187
Web Page Address: <http://www.gl.com/> ● E-Mail Address: gl-info@gl.com

Prices are subject to change

GL Communications Inc.

Digital Central Office Switch Simulator (DCOSS) Price List

Revised: April 13, 2015

DM060	Fax License (60 global faxes)	New generation boards only
DM480	Fax License (up to 480 global faxes)	New generation boards only
Miscellaneous		
SA017A	RJ48C to RJ48C Straight Cable	10 ft. length
SA017B	RJ48C to RJ48C Crossover Cable	10 ft. length
DX001	DCOSS Training (1 day)	hands on; exclusive of travel
DX002	DCOSS Configuration, Setup, Testing (per day)	exclusive of travel
DX004	Extended One Year Software Upgrade and Support	One year included in initial purchase
DX005	Second-Year Extended Hardware Warranty (does not include PC)	Please review Hardware Warranty Guidelines as outlined in the User Manual

Part Number	Description	Notes
Analog Phone Simulator (APS)		
APSCB-24	24-Port Analog Phone Simulator (APS), 115V P/S	Simulates a bank of 24 phones; A minimal configuration DCOSS is required – (DET002 and DR001) Requires DS011
APSCB-48	48-Port Analog Phone Simulator (APS), 115V P/S	Simulates a bank of 48 phones; A minimal configuration DCOSS is required – (DET004 and DR001) Requires DS011

818 West Diamond Avenue - Third Floor. Gaithersburg, MD 20878 ● (V) 301-670-4784 (F) 301-670-9187
 Web Page Address: <http://www.gl.com/> ● E-Mail Address: gl-info@gl.com

Prices are subject to change

GL Communications Inc.

Digital Central Office Switch Simulator (DCOSS) Price List

Revised: April 13, 2015

APSCBi-24	24-Port Analog Phone Simulator (APS), International 230V P/S	Simulates a bank of 24 phones; A minimal configuration DCOSS is required – (DET002 and DR001) Requires DS011
APSCBi-48	48-Port Analog Phone Simulator (APS), International 230 V P/S	Simulates a bank of 48 phones; A minimal configuration DCOSS is required – (DET004 and DR001) Requires DS011

Part Number	Description	Notes
	<i>Fax and Modem Analysis Software</i>	
FXT001 FXT002	GL Insight - Single Fax Analysis – TDM GL Insight - Single Fax Analysis – IP	Offline fax protocol and image analysis of captured PCM files w/dongle
VQT035	FXO RJ11 Hardware Tap / Audio Capture Software	Used for capturing Audio files from RJ11 connections for GL Insight Fax / Modem Analysis; requires Dual UTA or USB T1 E1 Analyzer; includes FXO RJ11 Hardware Tap
MDT001 MDT002	GL Insight - Single Modem Analysis – TDM GL Insight - Single Modem Analysis - IP	Offline modem protocol and data analysis of captured PCM files w/dongle

818 West Diamond Avenue - Third Floor. Gaithersburg, MD 20878 ● (V) 301-670-4784 (F) 301-670-9187
Web Page Address: <http://www.gl.com/> ● E-Mail Address: gl-info@gl.com

Prices are subject to change