


It is assumed that the tProbe™ T1 E1 Analyzer Hardware, Software, License and Warranty installations are already performed referring to the purchased Hardware Installation Guide.

Application Verification

- For this Loopback test verification, cross-connect **Port #1** and **Port #2** of the Hardware unit back-to-back with a **RJ-48C T1 E1 Crossover Cable**.



RJ48c Loopback Cable

- Double-click on the **tProbe™** () shortcut icon on the Desktop, the application should invoke without any errors.
- On the **Card Setting** dialog, for Port #1, double-click on the options and set the Loopback option as **No Loopback**, set the Termination as **Terminate**, and the clock as **Internal**.
- Now, click on **Set all Cards as selected** option to apply the same card settings on all available ports.


Port	Framing	Loopback	Termination	Clock	B8ZS	Cross-port
1	ESF (193E)	No Loopback	Terminate	Internal	On	Normal
2	ESF (193E)	No Loopback	Terminate	Internal	On	Normal

Port	Framing	Loopback	Termination	Clock	Cross-port
1	CCS	No Loopback	Terminate	Internal	Normal
2	CCS	No Loopback	Terminate	Internal	Normal

- Verify the **Sync and Alarm Status** between the ports are indicated in **Green** ✓ in **T1/E1 Alarms** pane. Click **Yellow Reset** button to reset the alarms.

Reset	All Ports	#1	#2
Sync Loss	✓	✓	✓
Bipolar Violation	✓	✓	✓
Carrier Loss	✓	✓	✓
Frame Error	✓	✓	✓
Blue Alarm	✓	✓	✓
Yellow Alarm	✓	✓	✓
AIS	✓	✓	✓

- From the main window, select **IntrusiveTest** → **Transmit Tone** this will invoke Tx Tone application.
- On the **Tx Tone** application, select **Timeslots** tab and click on **Select All** to select all the timeslots. Similarly, click on **Device Selection** tab and make sure that **Card #1** is selected.
- Now, go back to the **Tx Tone** tab and make sure that under **Tone Frequencies** the 1st tone option is set to **1004 Hz** and Tone Power Level dBm is set to **-10 dBm**.
- Click on **Send** to transmit tone.
- From the main window, select **Monitor** menu and click on any one of the monitoring applications like Byte Value, Binary Byte Value, Signaling Bits, Power Level
- Select **Card #2** to observe the tone being received on all the timeslots.
- Now, from the main GUI, select **Monitor** → **Oscilloscope** to observe the received tone in graphical format. Set the Card number as **Card #2**, select the required timeslot, and set the Time Base to display the received tone frequency as required.



Troubleshoot

If there are any problems while conducting the above test, please troubleshoot with the following steps:

- Ensure that the additional **Warranty License** has been installed or if the Warranty License has been installed already, please contact GL to renew the warranty license.



- Check if the analyzer software invokes the following alarm errors, then, ensure that **T1 E1 Crossover cables** are properly plugged in.
- Check if the Card settings for **Termination** is set to **Terminate** mode for both the ports and click on **Reset** button to get the sync on both the ports.

T1/E1 Alarms				
Reset	All Ports	#1	#2	
Sync Loss	✗	✗	✓	
Bipolar Violation	H	✓	H	
Carrier Loss	✗	✗	✓	
Frame Error	H	✓	H	
Blue Alarm	✓	✓	✓	
Yellow Alarm	✓	✓	✓	
AIS	✓	✓	✓	

- Ensure that the **Power Adapter** is connected to the **tProbe™ T1 E1 Analyzer** and to the **AC Power** on the strip or Wall. Ensure that the Power Strip is **ON**.
- Make sure that the USB cable is securely connected to the **tProbe™ T1 E1 Analyzer** and to the USB 2.0/USB 3.0 Connector.
- Follow the detailed instructions in the **tProbe™ T1 E1 Analyzer Installation Guide**.
- If you are still having issues or have other questions call GL Communications Inc. @ **301 670 4784**.